

**PRODUCT  
DATA SHEET**

**Exclusive 370**  
Vinyl Collection

December 2014

**Type of flooring**

EN ISO 26986 **Vinyl Floorcovering**

**Class of use**

EN ISO 10874



Class

23

32

**Description**



	<b>EN ISO 24346</b> (Previously EN 428)	<b>3,70 mm</b>
	<b>EN ISO 24340</b> (Previously EN 429)	<b>0,35 mm</b>
	<b>EN ISO 24341</b> (Previously EN 426)	<b>24 m</b> <b>4+3+2m</b>
	<b>EN ISO 23997</b> (Previously EN 430)	<b>2,700 kg/m<sup>2</sup></b>

	<b>EN660-2</b> Abrasion resistance <b>≤2mm<sup>3</sup></b> (Class T according to EN 649)
	<b>ISO 4918</b> <b>OK</b> (EN 425) Castor wheel test
	<b>EN ISO 717/2</b> <b>ca. 17 dB</b> Impact sound absorption
	<b>EN ISO 24343-1</b> <b>≤ 0,20 mm</b> (Previously EN 433) Static indentation

**Other Characteristics**

	<b>ISO 105/B02</b> Light fastness	<b>≥ 6</b>
	<b>EN ISO 23999</b> (Previously EN 434) Dimensional stability	<b>≤ 0,40 %</b>
	<b>EN ISO 10456</b> (EN 12524) Thermal resistance for underfloor heating	<b>0,06 m<sup>2</sup>/kW</b>

	<b>Slip resistance</b> EN 13893 DIN 51130	<b>μ ≥ 0,30</b> <b>R10</b>
	<b>Recyclable</b>	<b>OK</b>
	<b>Chemical resistance</b>	<b>OK</b>

	<b>Fire Classification</b> EN 13501-1 <b>Cfl-s1</b> (glued over wooden panel) Report N° : <b>RA14-0053</b>
	<b>EN 1815</b> <b>≤ 2 kV</b> Static electrical propensity



**Exclusive 370**  
No. 0131-0008-DoP-2014-12  
<http://www.home.tarkett.com>  
Manufactured by: Tarkett GDL SA  
2, Op der Sang  
L-9979 Lentzweiler - Luxembourg  
EN 14041:2004



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.