


# STANDARD PLUS technical data

CERTIFICATION & CLASSIFICATION	STANDARDS	Standard Plus 2.0 mm	Standard Plus 1.5 mm
Type of floor covering	ISO 10581	Homogeneous, single layered vinyl flooring	Homogeneous, single layered vinyl flooring
Binder Content	ISO 10581	Type II	Type II
CE certification	EN 14041	Yes	Yes
Classification	ISO 10874	Commercial: 34 Industrial: 43	Commercial: 32 Industrial: 41

TECHNICAL CHARACTERISTICS	STANDARDS	Standard Plus 2.0 mm	Standard Plus 1.5 mm
PUR		Yes	Yes
Total thickness	ISO 24346	2.0 mm	1.5 mm
Total weight/m <sup>2</sup>	ISO 23997	3300 g	2400 g
Form of delivery	ISO 24341		
	Sheet (rolls)	Approx. 23 lx x 200 cm Art. no. 21003 ___ 3 digit colour number	Approx. 25 lx x 200 cm Art. no. 21004 ___ 3 digit colour number
	ISO 24342 Tiles (box)	50 x 50 cm 24 tiles / box = 6.0 m <sup>2</sup> Art. no. 21006 ___ 3 digit colour number	-
	Tiles (box)	61 x 61 cm 14 tiles / box = 5.21 m <sup>2</sup> Art. no. 21005 ___ 3 digit colour number	-

TECHNICAL PERFORMANCES	STANDARDS	Standard Plus 2.0 mm	Standard Plus 1.5 mm
Dimensional stability	ISO 23999	≤ 0.40 % for rolls ≤ 0.25 % for tiles	≤ 0.40 %
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B <sub>fl</sub> s1 ≥ 8 kW/m <sup>2</sup> Pass	Class B <sub>fl</sub> s1 ≥ 8 kW/m <sup>2</sup> Pass
Marine equipment	IMO FTPC Part 5 and 2 IMO Res. A653		-
Residual indentation	ISO 24343-1	Required value: ≤ 0.10 mm Best measured value: 0.04 mm	Required value: ≤ 0.10 mm Best measured value: 0.04 mm
Castor chair test	ISO 4918	Suitable	Suitable
Static electrical discharge	EN 1815	< 2 kV	< 2 kV
Total VOC emissions	AgBB/DIBt	≤ 10 µg/m <sup>3</sup> (after 28 days)	≤ 10 µg/m <sup>3</sup> (after 28 days)
Underfloor heating		Suitable – max. 27°C	Suitable – max. 27°C
Thermal resistance	EN 12667	Approx. 0.01 m <sup>2</sup> K/W	Approx. 0.01 m <sup>2</sup> K/W
Light fastness	EN ISO 105-B02	≥ level 6	≥ level 6
Chemical resistance	ISO 26987	Good resistance	Good resistance
Bacteria resistance	ISO 846: Part C	Does not favour growth	Does not favour growth
Slip resistance	DIN 51130 EN 13893	R9 ≥ 0.3	R9 ≥ 0.3
Seam strength	EN 684	Average value: ≥ 240 N/50mm Individual values: ≥ 180 N/50mm	Average value: ≥ 240 N/50mm Individual values: ≥ 180 N/50mm
Colours		30 for rolls - 10 for tiles	12

The above information is subject to modification for the benefit of further improvement. (05/16).

CUSTOMS TARIFF: 482050000000F


Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

Standard Plus	NCS No.	Welding Rod No.	Standard Plus	NCS No.	Welding Rod No.	Standard Plus	NCS No.	Welding Rod No.	Standard Plus	NCS No.	Welding Rod No.	Standard Plus	NCS No.	Welding Rod No.
479	S 2010-Y40R	1287 160	492	S 3020-R90B	1291 210	498	S 3500-N	1287 027	913	S 2010-Y30R	1287 098	919	S 2005-R90B	1291 603
482	S 5005-Y50R	1287 373	493	S 4030-R90B	1287 281	499	S 5500-N	1287 394	914	S 3010-Y40R	1287 597	920	S 5030-R80B	1287 594
483	S 2010-Y20R	1287 039	494	S 2502-G	1294 701	500	S 8500-N	1287 314	915	S 5010-Y50R	1287 380	921	S 4030-G30Y	1287 559
484	S 2020-Y20R	1287 438	495	S 4000-N	1294 071	910	S 2005-Y50R	1292 319	916	S 1050-Y10R	1287 596	922	S 2040-G60Y	1287 592
485	S 2030-Y20R	1287 439	496	S 7005-Y20R	1287 333	911	S 3005-Y50R	1287 291	917	S 1070-Y20R	1287 595	923	S 3010-G10Y	1287 450
488	S 3060-Y80R	1287 441	497	S 1500-N	1287 338	912	S 1005-Y30R	1287 334	918	S 5020-R50B	1287 593	924	S 2000-N	1287 446

■ **WESTERN EUROPE:** Austria: Tarkett Holding GmbH, Niederlassung Wien – Tel. +43 1 47 88 062 ■ **Belgium:** Tarkett France Belux – Tel. +32 16 35 98 80 ■ **Denmark:** Tarkett A/S – Tel. +45 43 90 60 11 ■ **Finland:** Tarkett Oy – Tel. +358 9 4257 9000 ■ **France:** Tarkett SAS – Tel. +33 1 41 20 42 49 ■ **Germany:** Tarkett Holding GmbH, Bereich Objekt – Tel. +49 62 33 810 ■ **Greece:** Tarkett Monoprosopi Ltd – Tel. +30 210 6745 340 ■ **Italy:** Tarkett S.p.A. – Tel. +39 0744 7551 ■ **Luxembourg:** Tarkett GDL SA – Tel. +352 949 211 8804 ■ **Netherlands:** Tarkett Holding GmbH, Vestiging Nederland – Tel. +31 416 685 491 ■ **Norway:** Tarkett AS – Tel. +47 32 20 92 00 ■ **Portugal:** Tarkett SA – Tel. +351 21 427 64 20 ■ **Spain:** Tarkett Floors S.L. – Tel. +34 91 358 00 35 ■ **Sweden:** Tarkett Sverige AB – Tel. +46 771 25 19 00 ■ **Switzerland:** Tarkett Holding GmbH, Bereich Objekt Schweiz – Tel. +41 043 233 79 24 ■ **Turkey:** Tarkett Aspen – Tel. +90 212 213 65 80 ■ **United Kingdom:** Tarkett Ltd – Tel. +44 (0) 1622 854 040 ■ **EASTERN EUROPE:** Baltic Countries: Tarkett Baltics – Tel. +370 37 262 220 ■ **Czech Republic:** Tarkett France SAS, org. slozka – Tel. +421 248 291 317 ■ **Hungary:** Tarkett France SAS – Tel. +36 1 437 8150 ■ **Poland:** Tarkett Polska Sp. z o.o. – Tel. +48 22 16 09 231 ■ **Russian Federation:** ZAO Tarkett RUS – Tel. +7 495 775 3737 ■ **Slovakia:** Tarkett France SAS, org. slozka – Tel. +421 248 291 317 ■ **South East Europe:** Tarkett Trade d.o.o. – Tel. +381 21 7557 649 (44) 569 12 21 ■ **Ukraine:** Tarkett UA – Tel. +38 (0) 44 569 12 21 ■ **ASIA AND OCEANIA:** Australia: Tarkett Australia Pty Ltd – Tel. +61 2 88 53 12 00 ■ **China:** Tarkett Floor Covering (Shanghai) Co. Ltd. – Tel. +86 (21) 60 95 68 38 ext 841 ■ **North East Asia:** Tarkett Hong Kong Limited – Tel. +852 2511 8716 ■ **India:** Tarkett France (India Branch) – Tel. +91 11 4352 4073 ■ **South East Asia:** Tarkett Flooring Singapore Pte. Ltd. – Tel. +65 6346 1585 ■ **AFRICA:** Tarkett International: Tel. +33 1 41 20 41 01 ■ **MIDDLE EAST:** Tarkett Middle East: Tel. +961 1 51 3363/4 ■ **Israel:** Tarkett International: Tel. +33 1 41 20 41 01 ■ **NORTH AMERICA:** USA: Tarkett Inc. – Tel. +1 713 869 5811 / Johnsonite – Tel. +1 440 543 8916 ■ **Canada:** Tarkett Inc. – Tel. +1 450 293 173 ■ **LATIN AMERICA:** Brazil: Tarkett – Tel. 55 12 3954 7108 ■ **Argentina - Chile - Uruguay:** Tarkett Latam Mercosur – Tel. +54 11 47 08 07 72 / +54 9 11 44 46 88 82 ■ **Bolivia - Colombia - Ecuador - Panama - Paraguay - Peru - Trinidad and Tobago - Venezuela:** Tarkett – Tel. +55 11 9 8410 9310 / +55 11 95494 0069 ■ **Mexico / Central America:** Tarkett Latam Mexico – Tel. +55 11 98410 9310



## Logistics Information



## Surface treatment



## General Information



According to European Classification ISO 10874



According to European Classification ISO 10874

