

# Dalflex Nova

## DESCRIPTION

Semi-flexible tile on the basis of modified polyolefin.  
Product standard : EN 654.

Technical data	Standards	Dalflex Nova
Classification	EN 685 domestic commercial	Classes : 23 31
Total thickness	EN 428	2,0 mm
Total weight	EN 430	3 850 g/m <sup>2</sup>
Abrasion Group	EN 660-1	M
Curl resistance to water	NF - EN 662	≤ 0,75 mm
Residual indentation	EN 433	≤ 0,10 mm
Dimensional stability	EN 434	≤ 0,25 %
Reaction to fire	NF P 92506 DIN 4102/14 EN 13501-1 ASTM E 648	M2 B1 B <sub>fl</sub> ≤ 1 Category 1
Surface flammability Smoke and toxicity	IMO RESOLUTION A653 (16) IMO RESOLUTION MSC 61 (67)	Meet the requirement Test report : WARRES N° 123 004 Test report : WARRES N° 123 005 MED certificate in progress
Resistance to cigarette burns		Good resistance
Electrostatic properties	EN 1815 EN 1081 IEC 1340-4-1	≤ 2 kV > 10 <sup>10</sup> ohms ASF Class 2
Light fastness	EN 20105-B02	≥ 6/8
Chemical resistance	EN 423	Good resistance
Thermal resistance	pr EN 12524	0,018 m <sup>2</sup> K/W
Underfloor heating		Suitable
Colours		8
Form of delivery	EN 427	Tiles : 0,30 x 0,30 m - 6,30 sqm/box

The above information is subject to modifications for the benefit of further improvement (10/02).

**For the PREPARATION OF THE SUBFLOOR, STORAGE CONDITIONS AND USE, see instructions printed on the back of the box.**

## INSTALLATION

Use same batch number for each continuous surface. Adhere with an acrylic adhesive emulsion recommended by Tarkett Sommer (apply 250 to 300 g/m<sup>2</sup>) or with a solvent free bituminous adhesive (apply 120 to 150 g/m<sup>2</sup>). Place the tiles edge to edge at 90° (tessellate), press firmly by hand.

## CLEANING

**First use:** apply 2 - 3 coats of an acrylic emulsion polish.

**Daily cleaning:** simply mop with a small amount of neutral detergent diluted in clean warm water. Rinse with clean water.

**Periodical cleaning:** once a week, spray regenerating with a small amount of neutral detergent diluted in clean warm water using a scrubbing machine fitted with a red cleaning pad. Rinse with clean water.

**Note:** rubber-based caps or rollers may lead to permanent marks: replace them with plastic caps or attach protective felt. Also put protective felt under the legs of wooden furniture.